



FLINT & WALLING

Zoeller Family of Water Solutions™

“EK” Shallow Well Jet Pump Tank Mounted Systems

COMPLETE SYSTEM INCLUDES:

- Heavy cast iron CSA approved shallow well jet pump.
- Capacitor start motor with thermal overload protection. Dual voltage motor is factory connected for 115 volts. Spade connectors enable quick voltage change to 230 volt service.
- Horizontal Air-E-Tainer® pre-charged pressure tank with plumbing fitting between pump and tank.
- Pressure switch factory preset to 20-40 PSI.



“EK” SHALLOW WELL TANK MOUNTED SYSTEMS

Model	HP	Tank Type	Approximate Dimensions - Inches			Ship Weight
			Length	Width	Height	
EK05SAT25H	1/2	Horizontal	24.5	17.25	33.5	76 Lbs.
EK07SAT44H	3/4	Horizontal	24.5	17.25	33.5	76 Lbs.

Model	Suction Lift Ft.	Pressure Switch Setting PSI	Capacities Gpm At Discharge Pressure PSIG				Suction & Discharge
			20	30	40	50	
EK05SAT25H 1/2 HP 115/230V	5	20-40	10.5	9.5	5.8	4.0	1-1/4" X 3/4"
	15		7.6	7.3	4.5	2.5	
	25		4.5	4.2	3.5	2.0	
EK07SAT44H 3/4 HP 115/230V	5	20-40	15.5	15.0	10.0	5.8	1-1/4" X 3/4"
	15		11.9	11.7	9.1	3.8	
	25		6.0	5.8	5.2	2.0	